

FB3-F190-EXV25

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 80

WEIGHT (kg)

160

RESISTANCE

Bullet resistance: EN 1522 FB3
 Blast resistance: ISO 16933 EXV25

G2-F240

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 80

WEIGHT (kg)

180

RESISTANCE

Bullet resistance: BS 5051 - G2

FB4-F240-EXV25

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 80

WEIGHT (kg)

230

RESISTANCE

Bullet resistance: EN 1522 FB4
 Blast resistance: ISO 16933 EXV25

FB4-EXV28

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 80

WEIGHT (kg)

280

RESISTANCE

Bullet resistance: EN 1522 FB4
 Blast resistance: ISO 16933 EXV28

FB4-SR4

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 100

WEIGHT (kg)

300

RESISTANCE

Manual Attack Resistance:
 LPCB LPS1175 SR4 issue 8
 Bullet resistance: EN 1522 FB4

FB6

DIMENSIONS (mm)

H: 1900 - 2400
 W: 700 - 1200
 D: 100

WEIGHT (kg)

300

RESISTANCE

Bullet resistance: EN 1522 FB6

DATASHEET

STEEL SECURITY DOORS

STALWART DOORS

An external security door providing significant bullet, blast, fire and manual attack resistance. Standard or custom solutions to match project requirements are available upon request. Typical applications include plant rooms, cash centres, ATM pods, high-security areas and back-of-house applications.

MAIN FEATURES

- Standard certified doors include door leaf, door frame and ironmongery
- Standard finish is Polyester Powder Coating RAL7015 Slate Grey
- Standard opening direction is outwards, towards the attack side
- Door leaf and frame are finished in Polyester Powder Coating RAL7015 Slate Grey
- Surelock McGill locks are offered where applicable. SL313 is a 3 point lock, key entry with cylinder guard, thumb turn and lever handle exit
- Where applicable the Yale W3501 door closer is offered but other options are available upon request

OPTIONAL

- Other finishes are available from the RAL palette
- Kick plates, push plates and D handles are available where applicable and have a grained stainless steel finish
- Alternatives can be offered to the Surelock McGill locks where applicable
- Alternatives can be offered to the Yale Door Closers where applicable
- Blast resistance ISO16933 - EXV25 relates to 100kg of explosive at 25m attaining category C
- Blast resistance ISO16933 - EXV28 relates to 500Kg of explosive at 28m attaining category B



LPS 1175: Issue 8
 Cert/LPCB ref. 1617b (issue 1)

SERVICE &
 MAINTENANCE
 AVAILABLE

+44 (0) 1322 223 233

sales@safetell.co.uk safetell.co.uk